

cod. 39CM01A (optional)

* $F_{1i} =$

Isothermal end force at 100% Cu



p. 16



** $F_{1p} =$

Polytropic end force at 100% Cu


ACTIVE SAFETY



NE NG

CODE	Cu		L		L min		~Kg ~lb		PED 2014/68/EU	Force color code	P		F0 Initial force ± 5%		F1i End force*	F1p End force**
	mm	inch	mm	inch	mm	inch					bar	psi	+20°C daN	+68°F lb		
NE 16 x 2-010-B-...	10	0.39	65	2.56	55	2.17	0,05	0.11	✓							
NE 16 x 2-020-B-...	20	0.79	85	3.35	65	2.56	0,06	0.13	✓							
NE 16 x 2-030-B-...	30	1.18	105	4.13	75	2.95	0,07	0.15	✓	PR	12	174	4	9	1,57 x F0	2,03 x F0
NE 16 x 2-040-B-...	40	1.57	125	4.92	85	3.35	0,07	0.15	✓	GR	20	290	6	14	1,57 x F0	2,03 x F0
NE 16 x 2-050-B-...	50	1.97	145	5.71	95	3.74	0,08	0.18	✓	BU	40	580	11	25	1,57 x F0	2,03 x F0
NE 16 x 2-060-B-...	60	2.36	165	6.50	105	4.13	0,08	0.18	✓	RD	75	1088	21	47	1,57 x F0	2,03 x F0
NE 16 x 2-070-B-...	70	2.76	185	7.28	115	4.53	0,09	0.20	✓	YW	150	2175	42	95	1,57 x F0	2,03 x F0
NE 16 x 2-080-B-...	80	3.15	205	8.07	125	4.92	0,10	0.22	✓	BK	10-150	145-2175	3-42	7-95	1,57 x F0	2,03 x F0
NE 16 x 2-100-B-...	100	3.94	245	9.65	145	5.71	0,11	0.24	✓							
NE 16 x 2-125-B-...	125	4.92	295	11.61	170	6.69	0,12	0.26	✓							

P = nominal charging pressure



39DM16X2A

HOW TO ORDER

p. 31

INSTALLATION GUIDELINE

p. 205