



VERZE: d1: Hlubkově kaleno. Tělo vyhadzovače povrchově leštěno (g6).

HLAVA: popuštěná

MATERIÁL: 1.2510 (F522)

DŘÍK (d1): 60±2 HRC

TVRDOST HLAVY: 45±5 HRC

TEPELNÁ ODOLNOST: nejméně 220° C

R	R3	b3	l3	h3	h4	l1	l2	d1	d3	d2	l				
0,3	1,5	4	3	2,5	3	50	50	3	6	1,5	100				
							75				125				
							85				160				
							125				200				
						100	150	1,6	100	125	160	200	250		
														50	50
														75	75
														85	125
						75	125	1,8	100	125	160	200	250		
														50	50
														75	75
														85	125
						50	75	2	100	125	160	200	250		
														75	75
														85	125
														125	150
						100	150	2,5	100	125	160	200	250		
														125	150
														160	155
														50	50
						75	75	100	125	160	200	250	275		
														85	125
														125	150
														150	155

PŘÍKLAD OBJEDNÁNÍ
1702 - 1,6 × 3 × 125
 (1702 - d2 × d1 × l)

DALŠÍ VELIKOSTI VYHAZOVAČŮ A MATERIÁLŮ NA POPTÁNÍ